

Spindle Chiller / Gearbox Chiller (Dual-Pump Oil Chiller)



Specifications

Model		AO-25P2TS	AO-35P2TS	AO-50P2TS	AO-70P2TS
Cooling Capacity	W	2500	3500	5000	7000
	Kcal/h	2150	3000	4300	6000
Power Supply		Three Phase AC 220/380V 50Hz			
Rated Power (W)		1800	2200	2600	4500
Pump Flow Rate (L/min)		12	15	25	35
Outlet Pressure (Mpa)		0.5~1.5	0.5~1.5	0.5~1.5	0.5~1.5
Connection		Rp3/4	Rp3/4	Rp1	Rp1
Oil Temperature Range (°C)		Constant temperature control: 15 °C to 50°C Differential temperature control (ambient temperature compensation): +9 °C Control accuracy: ±1.5°C			
Ambient Temperature (°C)		5-45°C			
Noise Level		≤60 dB(A)		≤68 dB(A)	
Protection Rating		IP44	IP44	IP44	IP44
Oil Tank Capacity (L)		30	30	40	40
Dimensions (with Oil Tank) (mm)		425 ×500 ×950	425 ×500 ×950	480 ×550 ×1200	675 ×545 ×1265
Weight (with Oil Tank) (kg)		70	75	90	100